



STAINLESS STEEL WHEEL SIMULATORS

Light-duty D.O.T Approved No-Lug Mounting
Over-the-Lug Jam-Nut Retention System

PACKAGE CONTENTS

<u>Front Axle Set</u>	<u>Rear Axle Set</u>
<ul style="list-style-type: none">• 2 Front Wheel Simulators• 4 Jam-Nut Covers• 2 Center Decals• 2 Pop Out Centers	<ul style="list-style-type: none">• 2 Rear Wheel Simulators• 4 Jam-Nut Covers• 2 Center Decals• 1 Installation Tool

INSTALLATION INSTRUCTIONS

This system can be installed with the installation tool provided. No other tools are necessary. Do not use power tools for installation. It is recommended that the tool is stored in vehicle for future use.

ASSEMBLY DRAWINGS

1. Do not remove any lug nuts (unless needed in order to remove any wheel trim. Be sure to re-install lug nuts to factory specifications before continuing).
2. Determine correct placement of simulators required for proper hand hole and valve stem alignment.
3. Place liner on the wheel allowing the studs to clear the holes on the liner.
4. Hand-tighten Jam-nuts Covers onto the extended threads on the studs. Then use the installation tool to firmly secure onto the wheel.
5. Repeat 1~4 steps for each of the remaining wheels.
6. Apply decals.



am-Nut Cover

